





23YPTD

50Hz交流B-P性能数据/A.C. Core loss curves properties at 50Hz

| 磁感强度 B (T) | 铁损 P (W/kg) | 磁感强度 B (T) | 铁损 P (W/kg) |
|---------------|----------------|---------------|----------------|
| 0.45 | 0.059 | 1.61 | 0.709 |
| 0.50 | 0.071 | 1.62 | 0.722 |
| 0.55 | 0.084 | 1.63 | 0.735 |
| 0.60 | 0.098 | 1.64 | 0.748 |
| 0.65 | 0.112 | 1.65 | 0.762 |
| 0.70 | 0.128 | 1.66 | 0.777 |
| 0.75 | 0.145 | 1.67 | 0.791 |
| 0.80 | 0.164 | 1.68 | 0.807 |
| 0.85 | 0.183 | 1.69 | 0.823 |
| 0.90 | 0.204 | 1.70 | 0.840 |
| 0.95 | 0.226 | 1.71 | 0.857 |
| 1.00 | 0.250 | 1.72 | 0.875 |
| 1.05 | 0.276 | 1.73 | 0.895 |
| 1.10 | 0.302 | 1.74 | 0.915 |
| 1.15 | 0.333 | 1.75 | 0.936 |
| 1.20 | 0.363 | 1.76 | 0.959 |
| 1.25 | 0.396 | 1.77 | 0.983 |
| 1.30 | 0.429 | 1.78 | 1.009 |
| 1.35 | 0.465 | 1.79 | 1.037 |
| 1.40 | 0.504 | 1.80 | 1.067 |
| 1.45 | 0.545 | 1.82 | 1.136 |
| 1.50 | 0.591 | 1.85 | 1.248 |
| 1.55 | 0.641 | 1.87 | 1.337 |
| 1.60 | 0.697 | 1.90 | 1.506 |